



US007137255B2

(12) **United States Patent**
Schmotolocha et al.

(10) **Patent No.:** **US 7,137,255 B2**
(45) **Date of Patent:** **Nov. 21, 2006**

(54) **COMPACT SWIRL AUGMENTED
AFTERBURNERS FOR GAS TURBINE
ENGINES**

(75) Inventors: **Stephen N Schmotolocha**, Thousand Oaks, CA (US); **Donald H Morris**, Thousand Oaks, CA (US); **Robert J Pederson**, Thousand Oaks, CA (US); **Raymond B Edelman**, Woodland Hills, CA (US); **Calvin Q Morrison, Jr.**, Thousand Oaks, CA (US)

(73) Assignee: **United Technologies Corporation**, Hartford, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 44 days.

(21) Appl. No.: **11/095,647**

(22) Filed: **Mar. 31, 2005**

(65) **Prior Publication Data**

US 2006/0230764 A1 Oct. 19, 2006

Related U.S. Application Data

(60) Division of application No. 10/360,016, filed on Feb. 6, 2003, now Pat. No. 6,895,756, which is a continuation-in-part of application No. 10/243,961, filed on Sep. 13, 2002, now Pat. No. 6,820,411.

(51) **Int. Cl.**
F02K 3/10 (2006.01)
F02K 3/105 (2006.01)

(52) **U.S. Cl.** **60/761; 60/762**

(58) **Field of Classification Search** **60/737, 60/746, 747, 748, 749, 750, 761, 762, 763, 60/764, 765, 766, 39.5**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,605,608 A	8/1952	Barclay, Jr.
2,828,603 A	4/1958	Laucher
2,828,609 A	4/1958	Ogilvie
3,092,964 A	6/1963	Martin et al.
3,103,102 A	9/1963	Sargent et al.

(Continued)

FOREIGN PATENT DOCUMENTS

GB	754141	*	8/1956
GB	774059	*	5/1957


Primary Examiner—Ted Kim

(74) *Attorney, Agent, or Firm*—Harness Dickey & Pierce P.L.C.

(57) **ABSTRACT**

An afterburner apparatus that utilizes a novel swirl generator for rapidly and efficiently atomizing, vaporizing, as necessary, and mixing a fuel and an oxidant. The swirl generator converts an oxidant flow into a turbulent, three-dimensional flowfield into which the fuel is introduced. The swirl generator effects a toroidal outer recirculation zone and a central recirculation zone, which is positioned within the outer recirculation zone. These recirculation zones are configured in a backward-flowing manner that carries heat and combustion byproducts upstream where they are employed to continuously ignite a combustible fuel/oxidizer mixture in adjacent shear layers. The recirculation zones accelerate flame propagation to allow afterburning to be completed in a relatively short length. Inherent with this swirl afterburner concept are design compactness, light weight, lower cost, smooth and efficient combustion, high thrust output, wide flammability limits, continuous operation at stoichiometric fuel/oxidizer mixture ratios, no combustion instabilities, and relatively low pressure losses.

23 Claims, 23 Drawing Sheets



U.S. PATENT DOCUMENTS

3,575,384 A	4/1971	Sachs		4,896,502 A	1/1990	Ravel et al.	
3,675,419 A *	7/1972	Lewis	60/749	4,919,364 A	4/1990	John et al.	
3,701,255 A	10/1972	Markowski		5,240,404 A *	8/1993	Hemsath et al.	
3,901,028 A	8/1975	Leingang		5,251,447 A *	10/1993	Joshi et al.	
3,925,022 A	12/1975	Verdouw		5,311,735 A *	5/1994	Orlando	
3,977,353 A	8/1976	Toyama		5,319,923 A *	6/1994	Leonard	
4,170,111 A *	10/1979	Lewis et al.	60/762	5,411,394 A *	5/1995	Beer et al.	
4,185,457 A	1/1980	Parker et al.		5,511,970 A *	4/1996	Irwin et al.	
4,263,780 A	4/1981	Stettler		5,575,971 A *	11/1996	Bond	
4,343,147 A	8/1982	Shekleton		5,685,142 A *	11/1997	Brewer et al.	
4,461,146 A	7/1984	DuBell		5,845,480 A *	12/1998	DeFreitas et al.	
4,470,262 A	9/1984	Shekleton		6,301,900 B1 *	10/2001	Mandai et al.	
H000019 H *	2/1986	Carlson		6,820,411 B1 *	11/2004	Pederson et al.	60/229
4,598,553 A	7/1986	Saito et al.		6,895,756 B1 *	5/2005	Schmotolocha et al.	60/761
4,648,571 A	3/1987	Gerhardt		6,907,724 B1 *	6/2005	Edelman et al.	60/225
4,686,826 A	8/1987	Koshoffer et al.		6,968,695 B1 *	11/2005	Schmotolocha et al.	60/767

* cited by examiner




Fig-1




Fig-2







Fig-3








Fig-7




Fig-8





Fig-9

Fig-9A






Fig-10




Fig-10A





Fig-11






Fig-14




Fig-15




Fig-16




Fig-17




Fig-18




Fig-19




Fig-20




Fig-21




Fig-22




Fig-23




Fig-24




Fig-24A




Fig-25




Fig-26




Fig-27




Fig-28




Fig-29




Fig-30




Fig-30A




Fig-31






Fig-32






Fig-35A




Fig-36




Fig-37




Fig-38




Fig-39




Fig-40
PRIOR ART




Fig-41




Fig-41A

1

COMPACT SWIRL AUGMENTED AFTERBURNERS FOR GAS TURBINE ENGINES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a division of U.S. application Ser. No. 10/360,016, filed Feb. 6, 2003 entitled "Compact Swirl Augmented Afterburners For Gas Turbine Engines", now U.S. Pat. No. 6,895,756, which is a continuation-in-part of U.S. application Ser. No. 10/243,961, filed Sep. 13, 2002 entitled "Compact, Lightweight High-Performance Lift Thruster Incorporating Swirl-Augmented Oxidizer/Fuel Injection Mixing and Combustion", which issued as U.S. Pat. No. 6,820,411 on Nov. 23, 2004. Other features of the present invention are discussed and claimed in U.S. application Ser. No. 10/360,469 entitled "Compact Lightweight Ramjet Engines Incorporating Swirl Augmented Combustion With Improved Performance" now U.S. Pat. No. 6,968,695 and in U.S. application Ser. No. 10/360,168 entitled "Combined Cycle Engines Incorporating Swirl Augmented Combustion for Reduced Volume and Weight and Improved Performance" now U.S. Pat. No. 6,907,724.

FIELD OF THE INVENTION

The present invention generally relates to improvements in afterburners and more particularly to an afterburner having an improved fuel/oxidizer mixing and combustion apparatus, while being shorter, lighter and lower in cost.

BACKGROUND OF THE INVENTION

Due to hot-structure temperature limitations, conventional gas turbine engines for fixed wing military aircraft are typically unable to fuel the combustor to stoichiometric fuel/air mixture ratios which results in considerably lower thrust output, and the hot gas exhaust leaving these engines contain large amounts of unused oxygen. Afterburners, not being temperature restricted, are employed to capitalize on the unspent oxygen by burning additionally injected fuel therein, thereby permitting the pilot to selectively generate additional thrust. The additional thrust capacity is typically required for take-off, brief periods of acceleration, supersonic flight and/or critical combat maneuvers.

Conventional afterburners typically include a diffuser, which slows down the hot exhaust gases leaving the gas turbine engine, and a plurality of spray rings or tubes which inject fuel into the passing oxygen-rich exhaust gases. Mixing of the afterburner-injected fuel and the hot exhaust gases is accomplished by high-pressure injection, penetration and atomization. A spark igniter or other suitable ignition source is employed to initiate combustion of the afterburner mixture, while bluff-body flameholders, such as V-shaped gutters that are mounted concentrically around or downstream of a tail cone portion of the diffuser, and their wakes stabilize the flame and sustain self-propagating afterburner combustion. The afterburner diameter is expanded, but not exceeding the main engine diameter, to mitigate thrust loss by decelerating the hot exhaust gases. A variable area nozzle is employed to maximize thrust output for both the lower-temperature exhaust during non-afterburning operation and the high-temperature exhaust during afterburning operation.

As is well known in the art, the capability to afterburn approximately doubles the length of a gas turbine engine and

2

entails a substantial weight penalty. While the weight and packaging issues of an afterburner equipped gas turbine engine are relatively smaller than a turbojet or turbofan engine having a comparable thrust output, there is a need in the art for a relatively more compact and fuel efficient afterburner arrangement.

SUMMARY OF THE INVENTION

In one preferred form, the present invention provides an engine assembly having a gas turbine engine and an afterburner apparatus. The afterburner apparatus is coupled to the gas turbine engine and includes a burner and a swirl generator. The swirl generator has an inlet housing, a swirl vane pack, a centerbody assembly, and a plurality of fuel injectors. The inlet housing is coupled to the inlet of the burner and defines a hollow interior volume that serves as a conduit through which at least a portion of the hot exhaust flow is conducted. The hollow interior volume intersects the burner inlet at a dump step wherein the afterburner housing has an inner dimension that is larger than that of the inlet. The swirl vane pack is disposed within the hollow interior volume and has a plurality of vanes that cooperate to change the velocity of the exhaust flow so that its velocity includes a substantial tangential velocity component. The centerbody assembly is coupled to the swirl vane pack and extends rearwardly therefrom. The plurality of fuel injectors are coupled to at least one of the inlet housing, the swirl vane pack and the centerbody assembly and dispense the fuel therefrom. The swirl generator converts the oxygen-rich, hot core engine exhaust into a swirling, three-dimensional flowfield, a first portion of which flows over the dump step to form an outer recirculation zone and a second portion of the flowfield forms a central recirculation zone that is anchored by an aft end of the centerbody assembly. A first portion of the fuel mixes with the first portion of the flowfield to fuel the outer recirculation zone, a second portion of the fuel mixes with the second portion of the flowfield to fuel the central recirculation zone, while the majority of the injected fuel feeds the respective shear layers and the non-recirculating core flowfield.

The afterburner apparatus of the present invention overcomes the aforementioned drawbacks through the use of a novel swirl generator that promotes rapid and efficient atomization and mixing of the fuel and the hot oxygen-rich exhaust gases. Self sustained ignition and efficient flame propagation is provided by the highly energetic recirculation zones coupled to the core flow through the high, swirl induced, turbulence in the shear layers that promotes very rapid combustion of the core flowfield mixture. Combustion can be completed in as little as one-fourth the length required in known afterburner devices.

Accordingly, the afterburner apparatus of the present invention is relatively shorter, lighter in weight and more fuel efficient than the known afterburner devices. No aero-intrusive instream flameholders are required, because the flame stabilization and propagation processes are controlled by the turbulence induced by the aerodynamics of the swirling flowfield. No aero-intrusive fuel injection rings are needed either, because the fuel is injected from the trailing edges of the swirl vanes and the centerbody. The long tail cone is eliminated and replaced with a short centerbody having an extendable and retractable tapered cone, and variable angle swirl vanes to accommodate afterburning and nonafterburning modes of operation to maximize thrust output at all flight conditions.

3

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Additional advantages and features of the present invention will become apparent from the subsequent description and the appended claims, taken in conjunction with the accompanying drawings, wherein:

FIG. 1 is a perspective view of a jet aircraft having a pair of lift thrust augmentors constructed in accordance with the teachings of the present invention;

FIG. 2 is a schematic illustration of a portion of the jet aircraft of FIG. 1;

FIG. 3 is a cut-away perspective view of a portion of the lift thrust augmentor illustrated in FIG. 1;

FIG. 4 is a longitudinal section view of a portion of the lift thrust augmentor;

FIG. 5 is an exploded perspective view of a portion of the lift thrust augmentor illustrating the elbow in greater detail;

FIG. 6 is a longitudinal section view of the elbow;

FIG. 7 is an exploded perspective view of a portion of the lift thrust augmentor;

FIG. 8 is an exploded perspective view of a portion of the lift thrust augmentor illustrating the centerbody hub assembly in greater detail;

FIG. 9 is a longitudinal section view of the centerbody hub assembly;

FIG. 9A is a schematic view of the swirl generator of the present invention illustrating several various centerbody assembly and wall injector fueling schemes;

FIG. 10 is a perspective view of a portion of the swirl generator illustrating the swirl vane pack in greater detail;

FIG. 10A is a partial top plan view of an alternately constructed swirl vane pack illustrating a profiled vane configuration;

FIG. 11 is an exploded perspective view of the swirl vane pack of FIG. 10;

FIG. 12 is an exploded sectional view of a portion of the swirl vane pack;

FIG. 13 is a longitudinal section view similar to that of FIG. 4 but illustrating a combustion event;

FIG. 14 is a partially broken away perspective view of a portion of a swirl generator constructed in accordance with the teachings of an alternate embodiment of the present invention;

FIG. 15 is a sectional view of a portion of a swirl generator constructed in accordance with the teachings of a second alternate embodiment of the present invention which illustrates an alternatively constructed centerbody hub assembly in detail;

FIG. 16 is an exploded perspective view of a portion of a swirl generator constructed in accordance with the teachings of a third alternate embodiment of the present invention which illustrates another alternatively constructed centerbody hub assembly;

FIG. 17 is a longitudinal section view of the centerbody hub assembly of FIG. 16;

FIG. 18 is a partially broken away side elevation view of a swirl generator constructed in accordance with the teachings of a fourth alternate embodiment of the present invention;

4

FIG. 19 is a perspective view of a portion of a swirl generator constructed in accordance with the teachings of a fifth alternative embodiment of the present invention which illustrates a vane for an alternative swirl vane pack with a plurality of fuel injection sites;

FIG. 20 is a partial sectional view of the vane of FIG. 19;

FIG. 21 is a perspective view of a portion of a swirl generator constructed in accordance with the teachings of a sixth alternative embodiment of the present invention which illustrates a vane for an alternative swirl vane pack with turbulator ramps and a plurality of fuel injection sites;

FIG. 22 is a partial sectional view taken through the vane of FIG. 21;

FIG. 23 is a front elevation view of a swirl generator constructed in accordance with the teachings of a seventh alternative embodiment of the present invention which illustrates a vane for a third alternative swirl vane pack having scallops;

FIG. 24 is a partial sectional view of a swirl generator constructed in accordance with the teachings of an eighth alternative embodiment of the present invention which illustrates an alternative inlet housing wherein a plurality of channels are formed into the inlet ramp;

FIG. 24A is a sectional view taken along the line 24A—24A of FIG. 24;

FIG. 25 is a partial sectional view of a swirl generator constructed in accordance with the teachings of a ninth alternative embodiment of the present invention which illustrates another alternative inlet housing illustrating the incorporation of fuel injection sites into the inlet ramp;

FIG. 26 is a partial sectional view of a swirl generator constructed in accordance with the teachings of a tenth alternative embodiment of the present invention which illustrates an alternative combustor illustrating the use of a quarl extension;

FIG. 27 is a partial sectional view of a swirl generator constructed in accordance with the teachings of an eleventh alternative embodiment of the present invention which illustrates another alternately configured centerbody hub assembly;

FIG. 28 is a partial sectional view of a swirl generator constructed in accordance with the teachings of a twelfth alternative embodiment of the present invention which illustrates another alternately configured centerbody hub assembly;

FIG. 29 is a front elevation view of a ramjet missile that incorporates a swirl generator constructed in accordance with the teachings of the present invention;

FIG. 30 is a longitudinal section view taken along the line 30—30 of FIG. 29;

FIG. 30A is a view similar to FIG. 30 but illustrating a swirl generator that employs flow guide vanes;

FIG. 31 is a longitudinal section view of a ramshell that incorporates a swirl generator constructed in accordance with the teachings of the present invention;

FIG. 32 is a partial longitudinal section view of a combined cycle engine having a plurality of ramjet engines that incorporate a swirl generator constructed in accordance with the teachings of the present invention;

FIG. 33 is a section view taken along the line 33—33 of FIG. 32;

FIG. 34 is a partial longitudinal section view of a second combined cycle engine having a plurality of ramjet engines that incorporate a swirl generator constructed in accordance with the teachings of the present invention;

FIG. 35 is a section view taken along the line 35—35 of FIG. 34;

5

FIG. 35A is a partial longitudinal section view similar of a third combined cycle engine having a ramjet engine that incorporates a swirl generator constructed in accordance with the teachings of the present invention;

FIG. 36 is a longitudinal section view of a rocket-based combined cycle engine constructed in accordance with the teachings of the present invention;

FIG. 37 is a rear elevation view of the rocket-based combined cycle engine of FIG. 37;

FIG. 38 is a perspective view of a portion of the rocket-based combined cycle engine illustrating the variable area throat in an open condition;

FIG. 39 is a perspective view similar to that of FIG. 38, but illustrating the variable area throat in a closed condition;

FIG. 40 is a longitudinal section view of an aircraft engine having a conventional afterburner;

FIG. 41 is a longitudinal section view similar to FIG. 40 but illustrating an afterburner that incorporates a swirl generator constructed in accordance with the teachings of the present invention; and

FIG. 41A is a longitudinal section view similar to that of FIG. 41 but illustrating an afterburner that utilizes a swirl generator with a collapsible centerbody cone.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to FIG. 1 of the drawings, an exemplary jet aircraft 8 is illustrated to include a pair of lift thrust augmentors 10 that are constructed in accordance with the teachings of the present invention. A conventional gas turbine engine 12 serves as the primary source of propulsive power for the jet aircraft 8, while the lift thrust augmentors 10 are selectively operable to produce thrust when the demand for thrust exceeds a predetermined threshold.

With additional reference to FIGS. 2 through 4, each lift thrust augmentor 10 includes an air delivery portion 20, a swirl generator 30 and a combustor/nozzle portion 40. When combined, the swirl generator 30 and combustor/nozzle portion 40 are also known as a compact swirl-augmented thruster (COSAT). The air delivery portion 20 includes a butterfly valve 50 and in the particular example provided, an elbow 60. It will be readily apparent to those skilled in the art that the air delivery portion 20 may be configured in any manner to package the lift thrust augmentor 10 into a particular application and as such, the elbow 60 may be omitted or the bend angle changed to suit the specific needs of a given application.

The butterfly valve 50 and the elbow 60 are coupled in fluid connection to the gas turbine engine 12. More specifically, hot high-pressure air is bled from the bypass fan 12a of the gas turbine engine 12 and diverted through a lateral jetscreen feed system (not specifically shown) to an attitude control system 70. The butterfly valve 50, which is normally maintained in a closed condition and coupled in fluid connection with the attitude control system 70, is opened to divert a predetermined amount (i.e., mass flow rate) of the hot high-pressure bleed air to the lift thrust augmentors 10. In the particular embodiment provided, about 30% of the airflow that is directed into the attitude control system 70 is redirected to the lift thrust augmentors 10 when the lift thrust augmentors 10 are operated to provide maximum thrust.

The air that passes by the butterfly valve 50 is routed through the elbow 60 to the swirl generator 30. As will be described in greater detail below, the swirl generator 30 injects fuel in to the air and promotes the efficient mixing of the air and fuel. A torch igniter 80, such as that described in

6

copending U.S. patent application Ser. No. 10/217,972 entitled "Torch Igniter", the disclosure of which is hereby incorporated by reference as if fully set forth herein, is employed to initiate a combustion event wherein the fuel/air mixture is burned in the combustor 40a of the combustor/nozzle portion 40. Those skilled in the art will appreciate that igniters, including electric spark igniters, plasma jet igniters, lasers and microwaves, may be employed in the alternative. As the construction of the combustor 40a is well known in the art, a detailed discussion of the combustor will not be provided herein. For example, those skilled in the art will appreciate that the combustor 40a may be wholly formed of a suitable high temperature material, or may utilize a perforated liner that facilitates air-cooling of the combustor 40a, or may utilize a wall that is partially or wholly comprised of fluid conduits that facilitate a flow of fluid through or about the combustor wall that operates to cool the combustor 40a during its operation.

Thereafter, hot combustion by-products are expelled through a nozzle 40b, such as a convergent nozzle (FIG. 4) or a convergent/divergent nozzle (FIG. 2), to produce thrust. It will be understood that the particular combustible mixture (i.e., a liquid fuel and air) that is utilized in this example is not intended to limit the scope of the disclosure in any way. In this regard, those skilled in the art will understand that any type of fuel (e.g., liquid, slurry, gas) and any type of oxidant (e.g., air, hydrogen peroxide, oxygen) may be utilized in the swirl generator and lift thrust augmentor of the present invention. Accordingly, when the term "mixing" is used in the context of a fuel/oxidant mixture, it will be understood to include atomization and vaporization if the fuel is not injected in gaseous state.

With reference to FIGS. 5 and 6, the elbow 60 is illustrated to turn the airflow 90 about 90° and is relatively constant in its cross-sectional area. The elbow 60 includes an elbow housing 94, a plurality of flow guide vanes 96, a pair of side covers 98 and an aerodynamic fairing 100. As will be readily apparent to one skilled in the art, the components of the elbow 60 may be fabricated out of any appropriate material, the selection of which is largely dependant on the temperature of the air entering the air delivery portion 20 (FIG. 2). In the particular example provided, the inlet temperature may be relatively high and as such, materials including Cress stainless steel series (e.g., 304, 321), Haynes 240, ceramic matrix composites (e.g., C/SiC, SiC/SiC, Si₃N₄, Al₂O₃/Al₂O₃) would be appropriate for the construction of the components of the elbow 60. As those skilled in the art will appreciate, various thermally protective coatings (e.g., ceramics) and/or heat transfer techniques that rely on a cooling effect provided by a working fluid (e.g., fuel, air) may additionally or alternatively be employed to render the components of the elbow 60 suitable for a given set of inlet conditions.

The elbow housing 94 is shown to include an inlet portion 102 and an outlet portion 104 that are interconnected by an arcuate turning portion 106. The elbow housing 94 may be unitarily formed via conventional processes such as casting or machining (from bar stock), or may be a multi-component fabrication that is fixedly coupled together as by welding. The lateral sidewalls 110 of the turning portion 106 include a plurality of concentric slots 112 that are formed there-through, while the endwall 114 in the turning portion 106 includes a fairing aperture 116. The fairing aperture 116 is sized to receive a portion of the aerodynamic fairing 100, as well as a conduit 120 (FIG. 4) that couples the swirl generator 30 to an ignition controller 122 (FIG. 4) that

actuates the lift thrust augmentor 10, as well as the fuel source 126 (FIG. 4) of the jet aircraft 8.

The flow guide vanes 96 are curved about a single axis and slide into the turning portion 106 through the concentric slots 112. Accordingly, the flow guide vanes 96 extend across the inner dimension of the turning portion 106 in a direction that is generally perpendicular to the direction of the air flow and concentric with the radius of the turn in the turning portion 106. The flow guide vanes 96 are also configured such that they extend between the inlet portion 102 and the outlet portion 104 of the elbow housing 94. Accordingly, the radially inward flow guide vanes, such as flow guide vane 96a, are relatively shorter than the radially outer flow guide vanes, such as flow guide vane 96d.

The leading and trailing edges 130 and 132, respectively, of the flow guide vanes 96 preferably engage the opposite ends of the concentric slots 112, while the opposite lateral sides 136 of the flow guide vanes 96 are abutted against the side covers 98, which are fixedly secured to the elbow housing 94 via a plurality of screws (not specifically shown). Additionally or alternatively, the flow guide vanes 96 may be welded in place to secure them in place within the concentric slots 112.

The flow guide vanes 96 are employed to mitigate air flow distortions and flow separation induced by the associated upstream butterfly valve 50 (FIG. 2) as well as to prevent further flow separation, the creation of secondary flows and large scale profile distortions due to centrifugal forces as the inlet flow undergoes the 90° turn through the turning portion 106. If unabated, secondary flows, separations and distortions tend to complicate the design and operation of the downstream fuel injection, alter the mixing effectiveness and provide stimuli for combustion instabilities. Consequently, the configurations of the air delivery portion 20 (generally) and the elbow 60 (specifically) provide a high degree of uniformity in the flow of air (i.e., a uniform axial airflow) to the swirl generator 30.

As best seen in FIG. 6, the flow guide vanes 96 cooperate with the elbow housing 94 to define a plurality of inlet flow channels 140. As the path that is defined by inlet flow channel 140a is relatively shorter between the inlet portion 102 and the outlet portion 104 as compared with the inlet flow channel 140e and as transient flow differences between the inlet flow channels 140 are highly undesirable, the flow guide vanes 96 of the particular embodiment illustrated are positioned in a radial direction in a manner that provides inlet flow channels 140 with dissimilar cross-sectional areas such that the inlet flow channels 140 produce a series of inlet flows that are relatively uniform in flow velocity. Accordingly, the inlet flow 150 to the swirl generator 30 has a velocity that is substantially completely defined by an axial velocity component.

In FIGS. 4 through 6, the conduit 120 that couples the swirl generator 30 to the ignition controller 122 (FIG. 2) and the fuel source 126 (FIG. 2) is illustrated to extend through the endwall 114 of the turning portion 106, through a conduit aperture 154 in the flow guide vane 96d and out the outlet portion 104 of the elbow housing 94 where it is coupled to the swirl generator 30. The presence of the conduit 120 in the interior of the turning portion 106 would ordinarily initiate a flow separation, which as mentioned above, reduces the effectiveness and efficiency of the lift thrust augmentor 10. The aerodynamic fairing 100, however, is employed to reduce or eliminate altogether, the flow separations that would be induced by the presence of the conduit 120.

In the example provided, the aerodynamic fairing 100 includes a hollow hub 156 and an airfoil portion 158 that is coupled to the hub 156. The conduit 120 extends through the hollow interior of the hub 156 and may be coupled thereto by any appropriate retaining means, including an interference fit (e.g., shrink fit or press fit), brazing and welding. The airfoil portion 158, which surrounds the conduit 120, extends in the in the down-wind direction in a tapered manner and terminates at its trailing edge 164 with a relatively small amount of trailing edge bluntness. Alternatively, the airfoil portion 158 may be configured to abut the windward side of the conduit 120. The airfoil portion 158 is positioned within the flow channel 140e so as to reduce or eliminate altogether the flow separations that would be induced by the presence of the conduit 120. The hub 156 and/or airfoil portion 158 may be fixedly coupled to the elbow housing 94 by any appropriate retaining means, including an interference fit (e.g., shrink fit or press fit), brazing and welding.

With reference to FIGS. 4 and 7, the swirl generator 30 is illustrated to include an inlet housing 200, a centerbody hub assembly 204, a swirl vane pack 206 and a wall injector assembly 208. In the particular example provided, the inlet housing 200 is illustrated to include an upper inlet housing segment 200a, which is coupled to and integrally formed with the outlet portion 104 of the elbow 60, an optional wall injection housing 228 (which will be described in detail, below) and an optional lower inlet housing segment 200b, which is coupled to the combustor/nozzle portion 40 and which includes an inlet extension 210 and an inlet ramp 212. Alternatively, the inlet housing 200 may be unitarily formed. Also alternatively, the upper inlet housing segment 200a may be separate from the outlet portion 104 of the elbow 60 and/or the lower inlet housing segment 200b, if included, may be integrally formed with the combustor/nozzle portion 40. Accordingly, those skilled in the art will appreciate that one or more of the upper and lower inlet housing segments 200a and 200b and the wall injection housing 208 may not exist as a discrete component. In the presently preferred configuration of the lift thrust augmentor 10, the upper inlet housing segment 200a is integrally formed with the elbow 60 so as to minimize the overall length of the lift thrust augmentor 10.

The inlet housing 200 defines a hollow interior volume 220 into which the centerbody hub assembly 204 extends. The injection of fuel into the lift thrust augmentor 10 is illustrated to include fuel injection through the wall 224 of the inlet housing 200 at a location forwardly of the inlet ramp 212. The sizing and purpose of the inlet ramp 212 will be discussed in greater detail, below.

As all fuel injection occurs downstream of the swirl vane pack 206, the presence of the inlet extension 210 effectively shifts the various points of fuel injection in an upstream direction relative to the inlet ramp 212 so as to provide additional time for the fuel to mix (i.e., for the liquid fuel of this example to atomize, mix and vaporize) prior to entering the combustor 40a. Those skilled in the art will appreciate that the amount of additional mixing time that is afforded by the inlet extension 210 is a function of its length. Those skilled in the art will also appreciate that the need for an inlet extension is based on the state of the air flow, such as the velocity, temperature, pressure and the characteristics of the fuel that is being used. Therefore, in some of the applications that we have conceived for the swirl generator 30, such as ramjets, the air flow is at a sufficiently high temperature such that even liquid fuels are rapidly mixed (i.e., atomized, mixed and vaporized), which permits the aft end of the

centerbody hub assembly **204** to be positioned so as to extend downstream of the inlet ramp **212** into the combustor **40a**.

In the particular example provided, wall injection is accomplished through the wall injector assembly **208**. The wall injector assembly **208** includes an annular wall injection housing **228** (which is considered to be part of the injection housing **200**) and a plurality of fuel injectors **230** that are circumferentially spaced about the wall injection housing **228**. The inside diameter of the wall injection housing **228** is equal in diameter to the inner diameter of the lower inlet housing segment **200b** so as to be flush and not to induce flow separations, etc. that would tend to impede the efficiency of the swirl generator **30**. The inside diameter wall injection housing **228**, however, is somewhat smaller in diameter than the inside diameter of the upper inlet housing segment **200a** for reasons that will be described in detail, below.

The wall injection housing **228** is disposed between the aft end of the upper inlet housing segment **200a** and the forward end of the lower inlet housing segment **200b**. Conventional Viton O-rings **238** or other sealing devices that are well known in the art are employed to seal the interface between the opposite faces of the wall injection housing **228** and the upper and lower inlet housing segments **200a** and **200b**. Threaded fasteners (not shown) are employed to fixedly couple the elbow **60**, the upper inlet housing segment **200a**, the wall injection housing **228**, the lower inlet housing segment **200b** and the combustor/nozzle portion **40** together.

In the example shown, the fuel injectors **230** comprise eight flush-mount simplex fuel injectors such as Woodward FST Simplex Injectors, which are commercially available from Woodward FST, Inc. of Zeeland, Mich. Those skilled in the art will appreciate, however, that other amounts and/or types of fuel injectors, including stand-off or wall flush simplex fuel injectors, orifice injectors or variable area poppet fuel injectors with variations in drop sizes and cone angles (i.e., solid or hollow cone) may also be used.

In FIGS. 7 through 9, the centerbody hub assembly **204** is illustrated to include the conduit **120** and a centerbody assembly **236**, which includes a forward centerbody **240**, a conduit retainer **242**, and an aft centerbody **244** and an igniter **246**. In the particular embodiment illustrated, the igniter **246** is a conventional spark igniter which is commercially available from sources such as those that are manufactured by Champion Spark Plug Company of Toledo, Ohio. Accordingly, a detailed description of the construction of the igniter **246** will not be provided herein. Those skilled in the art will appreciate that other types of igniters, such as a plasma jet igniter (also well known in the art and commercially available from sources such as Unison Industries Inc. of Jacksonville Fla.), microwave ignition devices, and laser ignition devices may be employed as an alternative to a spark igniter.

As noted above, the conduit **120** extends through the elbow **60** (FIG. 4) to couple the swirl generator **30** (FIG. 4) to the ignition controller **122** (FIG. 4) and the fuel source **126** (FIG. 4). In the particular embodiment provided, the conduit **120** is a hollow tube into which an electrical cable **250** and a plurality of fuel conduits **252** are housed. The electrical cable **250** electrically couples the ignition controller **122** to the igniter **246** such that electrical energy is transmitted to the igniter **246** when the ignition controller **122** is actuated to permit the igniter **246** to produce a discharge arc (not shown). The fuel conduits **252** couple in fluid connection of the fuel source **126** to a plurality of fuel injectors in the aft centerbody **244**. Those skilled in the art

will appreciate, however, that a single fuel conduit (not shown) may be alternatively employed, wherein the single fuel conduit supplies fuel to a fuel manifold within or coupled to the aft centerbody **244** to which are coupled the fuel injectors. Also alternatively, the swirl generator **30** may be constructed without a discrete fuel conduit **252** wherein such function would additionally be provided by the conduit **120** that houses the electrical cable **250**. Those skilled in the art will appreciate that these fuel splits could alternatively be accomplished through a set of orifices that effectively limit the mass flow rate of fuel therethrough.

The forward centerbody **240** is a generally hollow structure having a central aperture **270** into which the conduit **120** is fixedly coupled, as through brazing for example. The exterior surface of the forward centerbody **240** includes an aerodynamically contoured leading surface **272** as well as a mounting flange **274** to which the swirl vane pack **206** is mounted. The aerodynamically contoured leading surface **272**, which is illustrated to be generally spherically shaped in the particular example provided, serves to guide the inlet flow **150** (FIG. 4) exiting the elbow **60** radially outwardly around the forward centerbody **240** and into the swirl vane pack **206**. The mounting flange **274** has a diameter that is generally smaller than the trailing edge of the aerodynamically contoured leading surface **272** to thereby create an abutting flange **278** at the intersection of the mounting flange **274** and the leading surface **272**. The aft end of the interior of the forward centerbody **240** includes a counterbored portion **280** that is configured to receive the conduit retainer **242**.

The conduit retainer **242** is an annular structure with an open center that is configured to receive therethrough portions of the igniter **246** and the electrical cable **250**. A plurality of conduit mounting apertures **284** are formed through the conduit retainer **242** and are sized to matingly receive an associated one of the fuel conduits **252**. The fuel conduits **252** are preferably fixedly coupled to the conduit retainer **242** in their associated conduit mounting apertures **284** through an appropriate joining process, such as brazing. Conventional threaded fasteners, such as socket head cap screws **290**, are preferably employed to fixedly but releasably couple the conduit retainer **242** to the forward centerbody **240**.

The aft centerbody **244** may be configured in several different manners to optimize the efficiency of the lift thrust augmentor **10** and tailor its thrust output to a desired thrust output level. In the particular example provided the aft centerbody **244** includes first and second injector rings **300** and **302**, respectfully, and an aft bluff boat-tail **304**.

A conventional Viton O-ring **310** or other well known sealing device is employed to create a seal between the first injector ring **300** and the aft face of the forward centerbody **240**. The first injector ring **300** has a generally hollow center through which the igniter **246** is received, and an outside diameter that is relatively larger in diameter than that of the mounting flange **274**. The first injector ring **300** is illustrated to include a plurality of circumferentially spaced apart fuel injectors **320**, such as simplex injectors having a flow number (FN) equal to about 8.5, which are commercially available from Woodward FST, Inc. of Zeeland, Mich. Those skilled in the art, however, will appreciate that other types of fuel injectors, including a plurality of orifices, could be additionally or alternatively employed. Although the injectors **320** are illustrated as being configured to inject fuel in a radially outward direction, those skilled in the art will appreciate that the fuel injectors **320** may be alternatively configured to inject fuel in an upstream direction, a down-

stream direction or any combination of the radially outward, downstream and upstream directions.

The fuel injectors **320** are coupled in fluid connection to a manifold **324** that is formed into the first injector ring **300**. In the example provided, the manifold **324** is coupled in fluid connection to an associated one of the fuel conduits **252** to receive fuel therefrom. Those skilled in the art will appreciate, however, that the manifold **324** could also be coupled in fluid connection to each of the fuel conduits **252**. A Viton O-ring **326** or other well known sealing device is employed to seal the interface between the conduit retainer **242** and the front face of the first injector ring **300**.

A conventional Viton O-ring **330** or other well known sealing device is employed to create a seal between the second injector ring **302** and the aft face of the first injector ring **300**. The second injector ring **302** has a generally hollow center that is at least partially threaded so as to threadably engage a threaded portion **336** of the igniter **246** in a conventional manner. The second injector ring **302** may include no fuel injectors (i.e., constitute a "blank" injector ring as shown in FIG. 9A), or may include a plurality of circumferentially spaced fuel injectors **340**, such as simplex or orifice injectors, depending on the desired output of the lift thrust augmentor **10**. Although the injectors **340** are illustrated as being configured to inject fuel in a radially outward direction (FIG. 8), those skilled in the art will appreciate that the fuel injectors **340** may be alternatively configured to inject fuel in an upstream direction, a downstream direction or any combination of the radially outward, downstream and upstream directions.

The second injector ring **302** may be keyed or otherwise aligned to the first injector ring **300** in any conventional manner to maintain the first and second injector rings **300** and **302** in a condition wherein they are aligned about a common axis. In this condition, the outer surface of the second injector ring **302** substantially coincides with the outer surface of the first injector ring **300** to thereby prevent the generation of any flow separations or discontinuities.

In the embodiments wherein the second injector ring **302** includes fuel injectors **340**, a manifold **344**, which is formed into the second injector ring **302**, is employed to couple in fluid connection the fuel injectors **340** to an associated fuel conduit **252**. The manifold **344** may be coupled in fluid connection to the manifold **324** of the first injector ring **300**, or to an aperture **345** that is formed through the first injector ring **300** as is shown in FIG. 8. The interface between the first and second injector rings **300** and **302** is sealed by a Viton O-ring **346** in an area proximate the aperture **345**.

The aft bluff boat-tail **304** includes a flange portion **360** and a flow-effecting portion **362**. The flange portion **360** abuts the aft face of the second injector ring **302** and includes a pair of apertures **364** through which conventional socket head cap screws **366** are received. The cap screws **366** extend through similar apertures formed in the first and second injector rings **300** and **302** and the conduit retainer **242** and threadably engage apertures (not shown) in the forward centerbody **240** to fixedly couple these components to one another. The flange portion **360** also includes a hollow center **370** into which a tip **246a** of the igniter **246** extends. The hollow center **370** is chamfered on its aft end so as to provide additional space about the tip **246a** for a flame kernel.

The flow-effecting portion **362** is coupled to the outer perimeter of the flange portion **360**. In the particular embodiment provided, the flow-effecting portion **362** is frusto-conically shaped and includes a plurality of circumferentially spaced apart fuel injectors **380** that are configured to

inject fuel in a predetermined direction. Like the second injector ring **302**, the flow-effecting portion **362** may be alternately configured to include no fuel injectors (i.e., constituting a "blank" bluff body). Although the injectors **380** are illustrated as being configured to inject fuel in an upstream direction, those skilled in the art will appreciate that the fuel injectors **380** may be alternatively configured to inject fuel in a radially outward direction, a downstream direction or any combination of the radially outward, downstream and upstream directions.

In the example illustrated, the flow-effecting portion has an initial outer diameter that matches the outer diameter of the first and second injector rings **300** and **302**. The flow-effecting portion **362** terminates at its aft end at a sharp edge **386** that operates to initiate flow separation and to anchor and radially extend the central recirculation zone **610** (FIG. 13) to increase its size and flameholding capabilities.

Although the centerbody hub assembly **204** has been illustrated thus far as being formed from a plurality of discrete components, those skilled in the art will appreciate that various known manufacturing techniques, including direct metal fabrication, may be employed so as to reduce the actual number of components that are utilized. For example, the forward centerbody **240**, the swirl vane pack **206** and the first injector ring **300** may all be unitarily formed, which would thereby eliminate the need for the conduit retainer **242**.

Referring to FIG. 9A, the swirl generator **30** of the present invention is schematically illustrated to show several of the various fueling options that may be employed. The fuel injectors **230** may comprise, for example, orifices A, flush-mount simplex injectors B or stand-off simplex injectors C. The fuel injectors of the aft centerbody assembly **244** (i.e., fuel injectors **320**, **340**, **380** and **840**) may include simplex injectors D or orifices E, or may be omitted in part (blank) as designated by reference letter F.

In FIGS. 4, and 10 through 12, the swirl vane pack **206** is illustrated to include a mounting hub **400**, a plurality of vanes **402** and a shroud **404**. In the particular example provided, the swirl vane pack **206** is an assembly wherein the components comprising the swirl vane pack **206** are fabricated, assembled and fixedly secured to one another. Those skilled in the art will appreciate, however, that alternative fabrication techniques may be employed to reduce the number of components that comprise the swirl vane pack **206**. For example, technologies such as hot isostatic pressing, casting and direct metal fabrication may be employed to form the swirl vane pack **206**, either wholly or partially, or in combination with the centerbody assembly **236** or portions thereof as described above.

The mounting hub **400** is an annular structure that is received over the mounting flange **274** (FIG. 9) of the forward centerbody **240** (FIG. 9) in juxtaposed relation with the abutting flange **278** (FIG. 9) of the forward centerbody **240** and the front face of the first injector ring **300** (FIG. 9). The cap screws **366** (FIG. 8) exert a clamping force that fixedly but removably secures the aft centerbody **244** to the forward centerbody **240**. As the mounting hub **400** abuts the mounting flange **274** and the front face of the first injector ring **300**, the clamping force is also transmitted between the abutting flange **278** and the front face of the first injector ring **300**, which operates to fixedly secure (both axially and radially) the mounting hub **400** therebetween.

The vanes **402** of the swirl vane pack **206** are configured with a swirl number that ranges from about 0.4 to about 1.2 so as to permit the combustor/nozzle portion **40** to achieve a combustor length-to-diameter (L/D) ratio (as measured

13

from a plane at which the dump step **636** in FIG. **13** to the throat of the nozzle portion **40b**) that is less than about 2.0, and preferably less than about 1.6 and more preferably about 1.0 or less. In the particular example provided, we utilized twelve vanes **402** having a straight configuration that is skewed to the centerline of the mounting hub **400** so as to provide a swirl number of 0.54. Those skilled in the art will appreciate that various other vane configurations may alternatively be employed, including vanes with different skew angles and/or an arcuate or helical profile (FIG. **10A**). As the swirl vane pack **206** is comprised of a plurality of discrete components, the vanes **402** are configured with tabs **410a** and **410b** on their opposite ends. The radially inward tabs **410a** are configured to engage apertures **412** that are formed on the opposite faces of the mounting hub **400**. The tabs **410a** and the apertures **412** cooperate to align the vanes **402** to the mounting hub **400** so that the vanes **402** may be coupled to the mounting hub **400** in a conventional manner, such as brazing or welding.

The shroud **404** includes a pair of end caps **420** and a pair of circumferentially extending portions **422**. The end caps **420** include a plurality of apertures **424** that are configured to receive the radially outward tabs **410b** on the vanes **402**. In a manner similar to that of the apertures **412** of the mounting flange **274**, the apertures **424** cooperate to align the vanes **402** to the end caps **420**. The circumferentially extending portions **422** are disposed around the perimeter of the vanes **402** between the tabs **410b** and the end caps **420**, circumferentially extending portions **422** and vanes **402** are fixedly secured together, as through welding.

With reference to FIG. **4**, the swirl vane pack **206** is illustrated to be fixedly coupled to the centerbody hub assembly **204** in the manner described above and disposed between the wall injector assembly **208** and a recessed step **500** formed in the upper inlet housing segment **200a**. In this location, the trailing edges of the vanes **402** of the swirl vane pack **206** are located upstream of all fuel injection sites, which eliminates any potential for flashback which would damage the vanes **402**. The shroud **404** of the swirl vane pack **206** is preferably sized to engage in a press-fit manner the recessed step **500** in the lower inlet housing segment **200b** to thereby structurally couple the swirl vane pack **206** and the centerbody hub assembly **204** to the inlet housing **200**.

The swirl generator **30** is configured such that the vanes **402** impart tangential velocities to the axial inlet flow **150** to convert the inlet flow **150** into a spiraling, three dimensional swirling flow structure or flowfield **510** (FIG. **4**). The flowfield **510** has a dramatic effect on the rate of fuel mixing, atomization, droplet vaporization, flame propagation, combustion efficiency, combustion stability, combustion intensity and widens flammability limits. Those who are skilled in the art will appreciate that radial velocities will be affected by the swirling effect, but that the major impact of swirling effect concerns the aforementioned tangential velocity component.

With reference to FIG. **13**, the high tangential velocities produced by the vanes **402**, whether straight or profiled in their configuration, creates a very intense shear layer **600** and enhances the large scale vortex or central recirculation zone **610** that is generated and anchored by the bluff end **614** of the aft centerbody **244**, even at relatively low levels of swirl (i.e., a level of swirl that is greater than or equal to about 0.4). In the case of vanes **402** having a flat configuration, especially high shear stresses are created that promote very efficient mixing of the fuel that is introduced into the inlet housing **200** via the wall injector assembly **208** and

14

the injectors **320**, **340** and **380** in the aft centerbody **244** due to high intensity turbulence that is generated by the trailing edge vortices that are induced by the flow separation on the lee side of the vanes **402**. Combustion in the central recirculation zone **610** is initiated by a flame kernel **630** that is produced by the igniter **246** that is housed in the centerbody hub assembly **204**. Additionally or alternatively, igniters **80a** (similar or identical to igniter **246** or igniter **80**) may also be employed near the dump plane **636a**.

The inlet ramp **212**, which is optional, aids in increasing the size of the dump step **636** that occurs at the dump plane **636a**. In the particular example provided, the inlet ramp **212** helps to create a relatively large **900** dump step **636** at the transition between the inlet housing **200** and the inlet of the combustor **40a** that serves to considerably improve flame propagation rates and the combustor's operability limits. More specifically, the dump step **636** creates a toroidal outer recirculation zone **640** along the combustor wall that is initially ignited by a flame kernel that is produced by the torch igniter **80** or the igniter(s) **246** and/or **80a** (FIG. **4**). The length of the outer recirculation zone **640** is a function of the height of the dump step **636** and the strength of the swirl number of the swirl vane pack **206**. Generally speaking, for a given constant swirl number, the length, size and robustness of the outer recirculation zone **640** are directly related to the height of the dump step. The inlet ramp **212** and its shape not only provide a means to easily tune the flow height of the dump step **636** and the flow direction, but also increases the local flow velocities to thereby intensify the separated shear layer turbulence and increases the rate of mass entrainment of fuel into the shear layer. The ramp shape and reduced flow gap height also accelerates early merging of the shear layers **650** and **600** of the outer recirculation zone **640** and the central recirculation zone **610**, respectively, which is essential for combustors having a relatively short length. Those skilled in the art will appreciate that the shape of the ramp can be altered to change the maximum height and, therefore, the volume of the outer recirculation zone and the gaps between the outer and central recirculation zones.

Portions of the fuel that are dispensed by the fuel injectors **320**, **340** and **380** are employed to substantially fuel the central recirculation zone **610**, while portions of the fuel that are dispensed by the fuel injectors **230** of the wall injector assembly **208** are employed to fuel both the outer recirculation zone **640** and fuel the central recirculation zone **610**. Any portions of the fuel that is dispensed by the injectors **230**, **320**, **340** and **380** that is not employed to fuel the central or outer recirculation zones **610** and **640** is employed to generally fuel the main core flow **700**, which as those skilled in the art will appreciate, consists of the entire flow of combusting fuel and air except the central recirculation zone **610** and the outer recirculation zone **640**. The central recirculation zone **610** and the outer recirculation zone **640**, once formed, contain a fixed trapped mass. An exchange of mass occurs between each of the central and outer recirculation zones **610** and **640** and the core flow **700**, but there is no net change in mass for steady flow conditions in either of the central and outer recirculation zones **610** and **640**.

As each of the injectors **320**, **340** and **380** are coupled in a discrete manner to the fuel source **126**, the amount of fuel that is dispensed by the injectors **320**, **340** and **380** may be tailored in a desired manner to fine tune flame stabilization and combustion performance during throttling. Accordingly, the injectors **320**, **340** and **380** may be independently con-

15

trolled so as to provide a relatively wide range of flexibility to control combustor characteristics, depending on a particular application.

The shear layers **650** and **600** of the outer recirculation zone **640** and the central recirculation zone **610** provide reduced velocity regions to hold the flame, and maintain and propagate the combustion process. More specifically, the outer recirculation zone **640** and the central recirculation zone **610** provide flame stabilization and act as a robust ignition source for the core flow **700** by supplying heat and recirculated chemically reacting by-products, such as OH, H and O radicals, to the main fuel/air mixture of the combustor **40a**. In this regard, each recirculation zone carries the heat and chemically active species from the flame in the respective shear layer and recirculating flow volume upstream where they act to ignite the fresh combustible fuel/air mixture entering the shear layer to thereby provide a continuous pilot for the core flow **700**.

As noted above, the aft centerbody **244** of the swirl generator **30** may be configured in various different arrangements to achieve desired design parameters. For example, the aft centerbody **244** may be configured with a channeled aft bluff boat-tail **304a** as illustrated in FIG. **14**. The aft bluff boat-tail **304a** is generally similar to the aft bluff boat-tail **304** of FIG. **8**, except that it includes a plurality of channels **800** that are formed about the perimeter of the flow-effecting portion **362a**. The channels **800** are formed at an angle relative to the centerline of the aft bluff boat-tail **304a** that maintains the effective flow direction provided by the swirl vane pack **206**. Those skilled in the art will appreciate that other channels may be selected to control turbulent transport and mixing including ones that are opposite of the tangential direction provided by the swirl vane pack. The ramp-like geometry of the channels produces a spectrum of turbulence scales that enhances mixing to promote flame intensity and propagation from the central recirculation zone **610** into the core flow **700** (FIG. **13**). Like the aft bluff boat-tail **304**, the aft bluff boat-tail **304a** may include one or more fuel injectors, or may have a "blank" configuration (i.e., a configuration without one or more fuel injectors).

In the embodiment of FIG. **15**, the aft centerbody **244b** is illustrated to be generally similar to the aft centerbody **244** of FIG. **9**, except that it does not include a discrete bluff body. In this regard, the second injector ring **302** essentially forms a bluff body as the aft centerbody **244b** terminates abruptly at the rear face of the second injector ring **302**.

The embodiment of FIGS. **16** and **17** is generally similar to that of FIG. **15** except that the igniter **246** has been replaced with a fuel injector **840**, such as a simplex atomizer having, for example, a 100° spray angle. The fuel injector **840**, like the previously discussed fuel injectors that are housed in the aft centerbody **244**, is individually coupled to a fuel conduit **252** so as to permit the fuel injector **840** to be selectively deployed. In this embodiment, the central recirculation zone is also ignited by the flame kernel that is produced by the torch igniter **80** and/or the igniter **80a** that are described above as initiating combustion in the outer recirculation zone.

Another embodiment is illustrated in FIG. **18** wherein the fuel injectors in the wall of the inlet housing **200f** are replaced by a plurality of cross-flow strut injectors **900**. Each of the cross-flow strut injectors **900** is swaged into the aft centerbody **244f** for structural support and coupled in fluid connection to fuel conduits **906** that extend through the inlet housing **200f**. Each cross-flow strut injector **900** has a plurality of orifices **910** that promote atomization of the fuel

16

flowing therethrough. Additionally, this embodiment includes a channeled aft bluff boat-tail **304f** and a center-mount fuel injector **840**.

The embodiment of FIGS. **19** and **20** provides a fuel injection scheme that is very similar to that of the embodiment of FIG. **18**. Instead of cross-flow strut injectors, however, this embodiment utilizes a plurality of fuel injection sites **1000a** that are formed into a trailing edge **1002g** of at least a portion of the vanes **402g** of the swirl vane pack. The injection sites **1000a** are coupled in fluid connection to an associated fuel conduit that extends through the conduit **120** (FIG. **4**); a plurality of internal channels **1004** in the vanes **402g** serve to transmit the fuel through the vanes **402g** to the injection sites **1000a**. As illustrated in FIG. **20**, each of the injection sites **1000a** is an orifice **1006** that has an appropriate length to diameter ratio and which is formed into the trailing edge **1002g** at a predetermined angle relative to an axis of the vane **402g**. Although the injection sites **1000a** are illustrated as being generally oriented in a downstream direction, those skilled in the art will appreciate that additionally or alternatively the injection sites could also be skewed to the axis of the vane **402g**. Additionally or alternatively, the holes **1006** may be formed on a lateral surface of the vanes **402g** to inject fuel in a desired direction (see, e.g., injection sites **1000b** and **1000c** in phantom in FIG. **20**, which are also formed with an appropriate orifice length to diameter ratio). Despite the complexity of the vane arrangement, this embodiment is advantageous in that the exterior surfaces of the vanes **402g** form an effective means for transferring heat from the air flow to the fuel in the vanes **402g** which operates to cool the swirl vane pack as well as to increase the temperature of the fuel that is injected, which tends to increase the rate by which the fuel is mixed (i.e., improve atomization, decrease the size of the droplets in the fuel spray and directly increase the rate of droplet vaporization).

The embodiment of FIGS. **21** and **22** is generally similar to that of FIGS. **19** and **20**, except that an array or row of turbulator ramps **1050** are formed or mounted onto at least a portion of the vanes **402h** of the swirl vane pack **206** to further enhance mixing. The turbulator ramps **1050** and the channels **1052** that are formed between each pair of turbulator ramps **1050** are employed to generate vortices that emanate from the trailing edge **1002h** of the vanes **402h**; the vortices enhance turbulent transport and provide highly controlled fine scale mixing. Like the previous embodiment, a plurality of fuel injection sites **1000h** that are formed into a trailing edge **1002h** (i.e., into the tubulators **1050**) which are coupled in fluid connection to an associated fuel conduit that extends through the conduit **120** (FIG. **4**); a plurality of integrally formed channels **1002h** in each of the vanes **402h** serve to transmit the fuel through the vanes **402h**. Those skilled in the art will also appreciate that the turbulators **1050** may also be utilized in vane configurations that do not inject fuel (i.e., in vanes without injection sites formed therein).

The example of FIG. **23** is generally similar to that of FIG. **4**, except that the trailing edge **1002i** of the vanes **402i** includes a plurality of scallops **1100** rather than turbulators. The scallops **1100** are illustrated to be formed in a uniform manner wherein the crest **1102** is relatively wider than the root **1104**. Those skilled in the art will appreciate, however, that the scope of the present invention is not limited to any particular scallop pattern. Those skilled in the art will appreciate, too, that the vanes **402i** may also be configured

17

with a plurality of fuel injection sites in the manner described above for the embodiments of FIGS. 19 through 22.

In the embodiment of FIGS. 24 and 24A, the inlet ramp 212j is illustrated to be generally similar to the inlet ramp 212 of FIG. 4, except that a plurality of channels 1150 are formed about the perimeter of the inlet ramp 212j. The channels 1150 are formed at a predetermined angle relative to the longitudinal axis of the inlet housing 200j and serve to enhance turbulent transport and fine scale mixing.

In the embodiment of FIG. 25, a plurality of circumferentially spaced apart fuel injection sites 1200 are formed about the circumference of the inlet ramp 212k. The fuel injection sites 1200 are operable for injecting fuel into the flow field which aids in flame stabilization and communication between the outer and central recirculation zones. As those skilled in the art will appreciate, the channels of the previous embodiment may additionally be incorporated into the inlet ramp 212k.

Those skilled in the art will appreciate that the wall of the combustor 40a in an area proximate to the outer recirculation zone tends to absorb a relatively large amount of heat during the combustion process. An optional quarl expansion 1250 may be provided as shown in FIG. 26 at the dump step 636. The quarl expansion 1250 is an annular element having a generally triangular cross section; the quarl expansion 1250 is employed to "fill" the backwards facing step at the dump plane such that the angle of the dump step 636 is reduced from 90°. The angle β of the quarl expansion 1250 may be varied in a known manner to affect the size of the central recirculation zone and the rate of heat transfer to the wall of the combustor 40a and the inlet housing 200.

The embodiment of FIG. 27 illustrates that the configuration of the centerbody assembly aft of the leading surface need not have the configuration of a right cylinder. In the particular embodiment illustrated, the portion of the centerbody assembly 236m aft of the leading surface 272m has a generally frusto-conical shape that is symmetrical about a longitudinal axis of the swirl generator 30m. Those skilled in the art should also appreciate that the portion of the centerbody assembly that is positioned aft of the leading surface may be other than conical (e.g., ogival). Those skilled in the art will also recognize that multiple fuel injection sites, similar to fuel injectors 320, 340, 380 and/or 840 of FIGS. 8 and 16 could be incorporated into the centerbody assembly 236m.

The embodiment of FIG. 28 is generally similar to the embodiment of FIG. 14 in that it includes two injection rings 1300 and 1302 that are positioned forwardly of the aft bluff boat-tail 304a. This embodiment differs from the embodiment of FIG. 14 in that the injection rings 1300 and 1302 are configured in a manner that is generally similar to that of the first injection ring 300 and a third injection ring 1304 is coupled to the aft end of the aft bluff boat-tail 304a. The injection ring 1304 is configured generally similar to that of the second injection ring 302 discussed above (i.e., includes fuel injectors and threadably engages the threaded portion 336 of the igniter 246). Additionally, the injection ring 1304 includes a plurality of optional grooves or channels 1310 that may be continuous with the grooves or channels of the bluff boat-tail body 800 which produces a spectrum of turbulent scales that enhance fuel and air transport and fine scale mixing to promote flame intensity and propagation from the central recirculation zone 610 into the core flow 700. As those skilled in the art will appreciate, the injection rings 1300, 1302 and/or 1304 may be "blank" and/or may include grooves or channels 1310 for producing fine scale

18

turbulence. Furthermore, the injection ring 1304 may be configured with an aft facing fuel injector such as that which is shown in FIGS. 16 and 17.

Ramjet Powered Applications

While the swirl generator of the present invention has been illustrated and described thus far as being a component of a lift thrust augmentor, those skilled in the art will appreciate that the invention, in its broader aspects, may be utilized in diverse other applications. In FIGS. 29 and 30, for example, the swirl generator 30 is illustrated in conjunction with a ramjet missile 2000.

In this example, the ramjet missile 2000 includes a forebody 2002, fins 2004, a booster engine 2006 and a ramjet engine 2010 having an air inlet 2012, the swirl generator 30 and a ramjet combustor/nozzle 2014. The forebody 2002 conventionally houses the payload (not shown), the fuel (not shown), batteries (not shown) and the control portion (not shown) of the ramjet missile 2000, while the fins 2004 conventionally stabilize and guide the ramjet missile 2000. The air inlet 2012 includes a movable or consumable port cover (not shown) that is selectively operable for sealing the air inlet 2012 and the swirl generator during the operation of the rocket booster engine 2006. In the example provided, the rocket booster engine 2006 includes a solid propellant 2018 that burns during a boost phase of the missile's operation; hot combustion by-products are expelled from the nozzle 2020 of the booster engine 2006 to generate thrust.

Subsequent to the boost phase of the missile's operation, the booster engine 2006 of the exemplary ramjet missile illustrated is ejected and the movable port cover is also ejected or consumed so as to permit air to flow into the air inlet 2012 so that the task of propulsion may switch from the rocket booster engine 2006 to the ramjet engine 2010. The speed of the missile 2000 and the configuration of the air inlet 2012 cooperate to induce an airflow 2026 through the air inlet 2012 that is directed toward the swirl generator 30. Alternatively, as illustrated in FIG. 30A, a plurality of flow guide vanes 96a (similar to the flow guide vanes 96 in the elbow 60) may be employed in the air inlet 2012 to provide an axisymmetric (i.e., uniform and axial) airflow to the swirl generator 30. Those skilled in the art will recognize that a chin inlet may be used followed by an annular air transfer duct that acts as an isolator and carries the air aft to the swirl generator 30 and the combustor of the ramjet combustor/nozzle 2014. In this case the air transfer duct will typically be S-shaped and may require guide vanes to straighten the flow as previously described. The swirl generator 30 is employed to generate a turbulent flowfield and to inject fuel therein in the manner described above. As in the example of the lift thrust augmentor, the swirl generator 30 operates to effect both an outer recirculation zone (proximate the dump step 2030 at the transition between the inlet housing 2032 and the inlet of the combustor/nozzle 2014), as well as a central recirculation zone (which is anchored by the aft end of the aft centerbody assembly 244).

Integration of the swirl generator 30 into the ramjet missile 2000 permits significant reductions to the L/D ratio of the combustor 2014a and substantial reductions in the overall length and weight of the ramjet missile 2000. Furthermore, the shortened combustor length provided by the swirl generator 30 allows the booster engine 2006 to be separately packaged and thus be ejectable as the propulsion switches from the booster engine 2006 to the ramjet engine 2010. A shorter and lighter weight missile, due to the swirl

generator 30, will offer significant maneuverability advantages over longer and/or heavier missiles due to a shorter turning radius capability. The CoSAT technology may also require a smaller booster due to ramjet take-over occurring at a lower Mach number and hence offer additional range capability and/or further improved agility.

Another application is illustrated in FIG. 31 wherein the swirl generator 30n is illustrated in conjunction with a ramshell 2300. The ramshell 2300 is a gun-launched, spin-stabilized projectile that employs the above-described ramjet technology to accelerate the ramshell 2300 to a velocity of about Mach 4 to about Mach 6 to extend the projectile range, minimize the time to target and maximize the penetration capability of the projectile. The ramshell 2300 includes a housing 2302, a projectile 2304, a plurality of inlet struts 2306, the swirl generator 30n and a combustor/nozzle portion 2308.

The housing 2302 is a hollow shell that is inwardly tapered at it's front end to define an air inlet 2310. The inlet struts 2306 are fixedly coupled to the interior of the housing 2302 and to the projectile 2304 to centrally mount the projectile 2304 in a forward portion of the housing 2302. As the ramshell 2300 is spin-stabilized, the inlet struts 2306 have a spiral shape to maintain alignment with the incoming air flow. The air flow is compressed through the inlet section 2310a and shocked to subsonic velocities near the aft end of the inlet struts 2306. While the projectile 2304 is illustrated as being a solid metallic rod, those skilled in the art will appreciate that any form of payload, including an explosive charge, may be employed in the alternative.

The swirl generator 30n is mounted on the aft end of the projectile 2304 and the swirl vane pack 206 serves to support the housing 2302 aft of the inlet struts 2306. Fuel injection is somewhat different from that of the swirl generator 30 of FIG. 4 in that the primary purposes of the swirl generator 30n are to augment the central recirculation zone (similar to the central recirculation zone 610 of FIG. 13) and to control the rate of mixing in the shear layer above the central recirculation zone and to control the rate of flame propagation into the core flow. Accordingly, wall injection is not employed in this embodiment, and the fuel injectors 2320 in the centerbody assembly 236n are fueled by a reservoir 2330 that is internal to the aft centerbody assembly 244n. The reservoir 2330 includes a pressurized bladder 2332 that surrounds the fuel 2334 to maintain the pressure of the fuel 2334 at sufficient levels during the operation of the ramshell 2300. The centrifugal force of the rotating fuel 2334 in the reservoir 2330 keeps the cooler, high density liquid fuel against the outer perimeter of the reservoir 2330 to assist in thermal protection of the combustor/nozzle portion 2308.

Fuel injection in the ramshell 2300 is preferably designed to maintain a somewhat fuel-rich condition in the central recirculation zone. As the main propulsive combustion initiates in the shear layer above the central recirculation zone, the level of mixing and heat release is controlled through the design of the swirl generator 30n so that only the air flow in the vicinity of the shear layer participates in combustion. Operation in this manner leaves the outer region near the interior side of the housing 2302 relatively cooler and protects the housing 2302 from the high heat flux near the throat of the combustor/nozzle portion 2308, before mixing of the hot combusting gases with the outermost air is complete.

FIGS. 32 and 33 illustrate yet another application of the swirl generator of the present invention. In this example, a swirl-augmented combined cycle engine 2400 is illustrated to include a core turbojet engine 2402, a plurality of ramjet engines 2404 that surround the core turbojet engine 2402 and a flow controller 2406. The core turbojet engine 2402 conventionally includes a low pressure compressor 2410, a high pressure compressor 2412, combustors 2414, an air bypass 2416 and a high pressure turbine 2418. As those skilled in the art will appreciate, the core turbojet engine 2402 may optionally include an afterburner 2402a and a variable area nozzle 2402b. Although the afterburner 2402a is illustrated to be a conventional afterburner having a fuel spray ring and a concentric V-gutter flameholder ring, those skilled in the art will appreciate that the afterburner 2402a may alternatively be configured in the manner illustrated in FIG. 41 and discussed in detail, below.

The ramjet engines 2404 are configured in a manner that is similar to the ramjet missile of FIGS. 29 and 30. Briefly, each of the ramjet engines 2404 includes an air inlet 2420, a swirl generator 30 and a ramjet combustor/nozzle 2430.

The flow controller 2406 is coupled to the core turbojet engine 2402 and includes a forward movable element or diverter 2440, which is employed to selectively control the intake of air into the core turbojet engine 2402 and the ramjet engines 2404, and an aft movable element or diverter 2442, which is employed to selectively close off the outlet of the core turbojet engine 2402 and the ramjet engines 2404. In the particular example provided, the forward and aft movable elements 2440 and 2442 are hingedly mounted to the housing 2450 of the core turbojet engine 2402 and pivotable between a first condition (illustrated in broken line), which closes off the air inlet 2420 and combustor/nozzle 2430, respectively, of each ramjet engine 2404, and a second condition (illustrated in solid line), which closes off the intake side of the low pressure compressor 2410 and the outlet of the high pressure turbine 2418, respectively. The forward and aft movable elements 2440 and 2442 may be moved through any of the various conventionally known means, including hydraulic actuators (not shown).

The core turbojet engine 2402 produces all of the propulsive power that is output by the swirl-augmented combined cycle engine 2400 from zero velocity through a predetermined transition-in velocity of, for example, at about Mach 2. Therefore, the forward and aft movable elements 2440 and 2442 are maintained in the first condition at speeds below the predetermined transition-in velocity.

At the predetermined transition-in velocity, the ramjet engines 2404 are activated to provide additional thrust. Flow entering the ramjet engines 2404 is subjected to additional ramjet compression 2460 and is further compressed to subsonic speeds in a transfer duct/shock isolator 2462. The air flow enters the swirl generator 30 and is converted into a highly turbulent flowfield into which fuel is injected in the manner described above. As the core turbojet engine 2402 is also producing thrust, the forward and aft movable elements 2440 and 2442 are maintained in a position between the first and second conditions. Additionally or alternatively, thrust augmentation by one or more of the ramjet engines 2404 may be accomplished via a bleed-burn process wherein air is tapped-off the high pressure compressor 2412, routed to the ramjet engines 2404 and burnt with added fuel (up to stoichiometric conditions) in the ramjet engines 2404. When the bleed-burn process is to be initiated, a valve 2463 is opened to permit air to flow through a duct 2464 into the

21

ramjet **2404**. Those skilled in the art will appreciate that a plurality of guide vanes **96b**, similar to guide vanes **96** discussed above, may be employed to provide a smooth, low loss entry of the bleed air into the ramjet engine **2404**.

When air speed reaches a predetermined ramjet takeover velocity of, for example, about Mach 3 to about Mach 4, the forward and aft movable elements **2440** and **2442** are positioned in the second condition and thrust production shifts entirely to the ramjet engines **2404**. The swirl ramjets **20** provide the required thrust from about Mach 3 to the cruise condition at speeds of up to approximately Mach 6.

As those skilled in the art will appreciate, the position of the forward and aft movable elements **2440** and **2442** may be controlled in response to flow sensors (not shown) in a selective manner to thereby affect the amount of air that is directed to the core turbojet engine **2402** and the ramjet engines **2404**. Alternatively, the forward and aft movable elements **2440** and **2442** may be controlled such that they move continuously from the first condition to the second condition at a predetermined rate upon the sensing of an air speed equivalent to the predetermined transition-in velocity or other event which would prompt the transition from one propulsion mode to another. By incorporating the swirl generator invention into the ramjet engine, this combined cycle engine concept can significantly reduce weight and size, yet provide high performance of the combustor and swirl ramjet concepts compared to other known turbine-based combined cycle engines using conventional ramjet systems. It also reduces the ramjet hot section length, thus reducing cooling requirements.

One unique feature of this concept is the aft-end valving that is accomplished by the aft movable element **2442**. The shape of the aft movable element **2442** is such that when positioned in the second condition, the aft movable element **2442** seals-off the aft end of the core turbojet engine **2402** and extends rearwardly in a manner wherein the surface **2442a** of the aft movable element **2442** defines one of the surfaces of the nozzle portion of the ramjet combustor/nozzle **2430**. Conversely, when the aft movable element **2442** is positioned in the first position, its surface **2442b** defines a portion of an expansion nozzle for the core turbojet engine **2402**.

Another swirl-augmented combined cycle engine **2400a** is illustrated in FIGS. **34** and **35**. The swirl-augmented combined cycle engine **2400a** is similar to the swirl-augmented combined cycle engine **2400** of FIGS. **32** and **33** in that it employs turbojet engines **2402**, ramjet engines **2404a** and a flow controller **2406a**, which selectively controls the input of air to the turbojet engine **2402** and the ramjet engine **2404a**. The swirl-augmented combined cycle engine **2400a**, however, is globally rectangular, segregated into a plurality of engine cells **2500**, with each engine cell **2500** including a turbojet engine **2402a**, a ramjet engine **2404a** and a flow controller **2406a**. Operation of each engine cell **2500** is identical to the operation of the swirl-augmented combined cycle engine **2400** of FIGS. **32** and **33** and as such, need not be described in detail. The plurality of engine cells **2500** are operated in a manner such that propulsion is regulated between the turbojet engines **2402** and the ramjet engines **2404a** in a uniform manner across the engine cells **2500** (i.e., transition from turbojet propulsion to ramjet propulsion is substantially simultaneous across all of the engine cells **2500**).

A third swirl-augmented combined cycle engine **2400b** is illustrated in FIG. **35A**. The swirl-augmented combined cycle engine **2400b** is a variant of the two previously described swirl-augmented combined cycle engine configura-

22

tions in FIGS. **32** and **34**, with one major difference being that the core engine **2402b** is coaxial with the ramjet engine **2404b**. In the example provided, the core engine **2402b** is a conventional gas turbine engine that features a co-axial afterburner **5020** having a swirl generator **30r**, thus replacing the long diffuser cone, one or more fuel spray rings and one or more concentric V-gutter flameholder rings.

The key features of the swirl generator include a variable angle swirl vane pack **206r**, a centerbody assembly **236r**, which includes a collapsible centerbody cone **5022**, a burner **5024**, which employs a quarl step **5026**, an array of first fuel injectors **5028**, which are integrated (e.g., embedded) into the base of the vanes **402r** of the swirl vane pack **206r** for main afterburning, an array of second fuel injectors **5030** (illustrated as injection orifices in the particular example shown) that are located on the aft centerbody assembly **244r** for ignition and piloting the afterburning, one or more igniters (not shown) that are located in the aft end or base of the aft centerbody assembly **244r** and/or in the recess of the quarl step **5026** and a variable area nozzle **5010**.

The swirl-augmented combined cycle engine **2400b** operates in a similar manner to those combined cycle engine concepts already described and therefore will not be discussed in detail other than to note that the swirl generator **30r** is employed for both the turbojet and ramjet engine cycles and therefore allows for a reduction in the overall length of the turbojet.

In operation, the combined cycle engine **2400b** employs a translating spike **5050** and an inner turbojet cowl **5060**. The translating spike **5050** is employed to control the shock-on-lip condition during supersonic speeds for both turbojet and ramjet operation, while the translating turbojet cowl **5060** cooperates with the translating spike **5050** to control the flow split during turbojet and ramjet mode operation (i.e., the portion of the intake air flow that is directed to the core turbojet engine **2402b** and the ramjet engine **2404b**). Although the forward portion of the translating spike **5050** is shown with a single cone angle, those skilled in the art will recognize that multiple cone angles may be employed to approximate an isentropic spike to thereby minimize total pressure losses generated by inlet shocks.

During the take-over of propulsion by the ramjet engine **2404b**, the translating spike **5050** is moved forwardly toward the inner turbojet cowl **5060** so as to close off the turbojet air intake **5084** and shift the air flow to the outer cowl inlet **5080** and into the air transfer duct/isolator **5070**. The valve **5040** is positioned in the outer air transfer duct/isolator **5070** in an open condition to allow air to flow directed into the swirl generator **30r** and through the nozzle **5010**. In this condition, the upstream portion of the turbine air bypass duct **5090** is closed off to prevent feedback and resonance using the same valve **5040** or an alternate valve **5045**. Those skilled in the art will appreciate that the valve **5040** is not required if the core turbojet engine **2402b** lacks an air bypass duct **5090**. The variable area nozzle **5010** is also repositioned during mode transition (i.e., the transition from turbojet propulsion to ramjet propulsion).

This swirl-augmented combined cycle engine **2400b** allows very compact engine packaging to reduce weight and length, yet provides high performance compared to known turbine based combined cycle engines that utilize conventional gas turbine afterburners and ramjet systems. The swirl generator **30r**/nozzle, which serves as the afterburner for the gas turbine engine and ramjet engine, also reduces the traditional ramjet engine hot section length and in turn

reduces cooling requirements to maintain structural and thermal integrity of the hardware.

Rocket-Based Combined Cycle

FIGS. 36 and 37 illustrate yet another application of the swirl generator of the present invention. In this embodiment, a rocket-based combined cycle engine 4000 is illustrated to include a housing 4002, one or more rocket engines 4004, a ramjet engine 4006 and a nozzle 4008. The housing 4002 houses the rocket engines 4004 and the ramjet engine 4006 and defines an air inlet 4020. The rocket engines 4004, which may be coupled to the housing 4002 such that they are located in the dump step 4022 (or quarl surface) and/or inside the aft end of the aft centerbody assembly 244p, may employ a liquid, slurry or solid fuel, depending upon the application and considerations for the altitude, range and speed that are mandated by the mission. The ramjet engine 4006 includes a swirl generator 30p which is generally similar to the swirl generator 30, except for the aforementioned rocket engine 4004 that is mounted to aft centerbody assembly 244p.

The rocket engines 4004 provide low speed thrust and additionally serve to pump air into the air inlet 4020. Air flowing through the air inlet 4020 is converted into a highly turbulent flow field into which fuel is injected and mixed (via the swirl generator 30p) in the manner described in detail above. In this regard, the air flowing through the air inlet is employed in an afterburning operation by the ramjet engine 4006 to augment the thrust that is generated by the rocket engines 4004 at all speeds. The pumping action is a result of the momentum transfer from the high velocity rocket exhaust and the entrained ambient air. The momentum transfer is the result of the turbulent exchange through the shear layers separating the exhaust of each rocket engine 4004 and the entrained air. Alternatively, the rocket engines 4004 may be used to rapidly accelerate the rocket-based combined cycle engine 4000 above a predetermined speed threshold after which propulsion is transitioned to the ramjet engine 4006.

Those skilled in the art will appreciate that a forward flap or diverter (not shown) may be employed to close-off the air inlet 4020 during low speed operation of the rocket-based combined cycle engine 4000 to effect pure rocket thrust generation up to a predetermined speed threshold after which propulsion is transitioned to the ramjet engine 4006. This mode of operation produces higher ramjet combustor pressures and associated thrust without the occurrence of backflow through the air inlet 4020 at lower speeds.

For optimum thrust in any mode of operation, the nozzle 4008 preferably includes a variable area throat 4030. The variable area throat 4030 is selectively configured to match the flow rate and back-pressure requirements of the rocket-based combined cycle engine 4000 for maximum and efficient thrust generation. Those skilled in the art will appreciate, however, that other nozzle throat concepts may be employed in the alternative, including consumable throat inserts, frangible throat inserts and ejectable throat inserts.

With additional reference to FIGS. 38 and 39, an exemplary variable area throat 4030 is illustrated to include a plurality of throat closure elements 4032 that are rotatable in the housing 4002 through an angle of about 90° between an open position, which is illustrated in FIGS. 37 and 38, and a closed position, which is illustrated in FIG. 39. Although only six elements are shown, those skilled in the art will appreciate that the number of throat closure elements 4032 may be varied to coordinate with the particular upstream

geometry of the a rocket-based combined cycle engine 4000. In the particular example illustrated, gaps 4034 are aligned to the six upstream rocket engines 4004 in the low speed mode to minimize erosion of the throat closure elements 4032 during the operation of the rocket engines 4004. When the throat closure elements 4032 are positioned in the closed position during the operation of the ramjet engine 4006, the area of the throat is substantially reduced.

In the embodiment illustrated, the throat closure elements 4032 rotate about an axis on a plane or facet on the inner surface of the housing 4002. The operational mechanism for rotating the throat closure elements 4032 may be housed in the housing 4002 or mounted on an adjacent structure (e.g., fins) to which the rocket-based combined cycle engine 4000 is mounted. Preferably, the throat closure elements 4032 are operated in opposed pairs so as to minimize rotational torques on the rocket-based combined cycle engine 4000 when the throat closure elements 4032 are moved between the open and closed positions.

When the throat closure elements 4032 are positioned in the closed position, the throat closure elements 4032 cooperate to provide the throat with an approximately circular shape; the extent to which the throat is circular is dependent upon the number of throat closure elements 4032 that are employed and whether or not the edges of the throat closure elements 4032 are contoured.

During the operation of the rocket-based combined cycle engine 4000, compressed air enters the air inlet 4020 and is directed to the swirl generator 30p. The air inlet 4020 also functions as an isolator at supersonic flight speeds where the air is further compressed and brought to subsonic speeds prior to being directed into the swirl generator 30p. The length of the air inlet duct 4020 is dictated by packaging requirements including fuel, propellants, warhead type (for missile applications), plumbing, controller(s), actuators and batteries. The minimum length of the air inlet duct 4020 is dictated by the isolation requirements that are necessitated during supersonic flight speeds.

During the combined operation of the rocket engines 4004 and the ramjet engine 4006, the swirl generator 30p functions to augment core flow mixing where flame stabilization is achieved in the recirculation zones in the backward facing areas between the exhaust nozzles 4004a of the rocket engines 4004 that are mounted in the outer step and/or an annular lip region at the end of the aft bluff boat-tail 304p. Special igniters are not required since the hot rocket exhaust will serve to ignite the fuel/air mixture for afterburning and ramjet operation. In addition, fuel and/or rocket propellant may be continuously bled through the otherwise idle rocket engines to help cool them and to prevent back flow of the ramjet's hot combustion by-products. The total engine flow passes through the variable area throat 4030 and is expelled to the atmosphere. Although the primary application anticipated for this technology is missile propulsion, those skilled in the art will appreciate that the rocket-based combined cycle engine 4000 may also be employed for aircraft propulsion where reduced weight and complexity would be desired.

Afterburning Turbojet Engine Applications

Another application of the swirl generator of the present invention is shown in FIG. 41, which illustrates the retrofitting of a compact swirl afterburner 5020 for a conventional afterburner 5000 of the military gas turbine engine 5002 that is shown in FIG. 40. Briefly, the military gas turbine engine 5002, which may be a turbojet engine or a

25

turbofan engine, includes a coaxially-mounted afterburner **5000** having a diffuser tailcone **5004** with one or more fuel spray rings **5006**, one or more concentric V-gutter flameholder rings **5008** and a variable area nozzle **5010**. The variable area nozzle **5010** is fully opened for afterburning operation and is reduced for non-afterburning operation.

Returning to FIG. **41**, retrofit of the military gas turbine engine **5002** entails the substitution of afterburner **5020** for the conventional afterburner **5000** (FIG. **40**). The afterburner **5020** includes swirl generator **30r** having a variable-angle swirl vane pack **206r**, a centerbody assembly **236r**, which has a collapsible centerbody cone **5022**, an expanding burner **5024**, which has a quarl step **5026**, an array of fuel injectors **5028** that are embedded into the base of the vanes **402r** for main afterburning, an array of circumferentially spaced apart fuel injectors **5030** (illustrated as injection orifices in the particular example illustrated) located on the aft centerbody assembly **244r** for ignition and piloting the afterburning, and one or more igniters (not shown) that are located in the aft end or base of the aft centerbody assembly **244r** and/or in the recess of the quarl step **5026**.

In order to maximize the benefits of the swirl augmentation provided by the swirl generator **30r**, attachment of the swirl generator **30r** should be as close as possible to the turbine exit plane. Accordingly, the length of the conical diffuser (i.e., the collapsible centerbody cone **5022**) can be shortened relative to the embodiment of FIG. **40**.

The hot gases, which consist mostly of air exiting the turbine and relatively cold air from the bypass fan of the main engine, enter the swirl generator **30r** where they are swirled and the streams are mixed to form a highly turbulent, three-dimensional flowfield. The fuel that is injected into this high shear stress-laden swirling flow is rapidly atomized and mixed. Atomization and mixing are controlled by a novel design of the swirl generator **30r**.

The swirling mixture of the afterburner fuel, hot turbine gases and colder bypass fan air are slowed down across the quarl step **5026** as the flow enters the combustor **5024**, and creates a central recirculation zone and an outer recirculation zone similar to the central recirculation zone **610** and outer recirculation zone **640** of FIG. **13**. The central recirculation zone is governed by the combined effects of the swirl strength (a characteristic of the variable-angle swirl vane pack **206r**) and the blunt aft end of the aft centerbody assembly **244r**. The outer recirculation zone is created by separation of the fuel/air mixture as it flows over the quarl step **5026**. Combustion in the afterburner **5020** is very robust, stable and highly efficient such that the energetic, high temperature by-products of the combustion event are expanded through the variable area nozzle **5010** to provide high levels of thrust.

During non-afterburning operation, the swirl generator **30r** serves as a channel between the main engine and the variable area nozzle **5010**. To avoid significant pressure losses due to the presence of the vanes **402r**, the variable-angle swirl vane pack **206r** is controlled such that the angle of the vanes **402r** is changed to 0° so as to remove the swirl from the flow and thereby maintain the axial character of exhaust flow. Vanes **402r** having a flat profile are presently preferred. As an alternative to the variable angle swirl vane pack **206r**, a two-position swirl vane pack (not shown) may also be employed. Also during non-afterburning operation, the collapsible centerbody cone **5022** that is attached to the aft centerbody **244r** is extended to create a flowfield with relatively greater aerodynamic efficiency and relatively lower pressure losses.

26

With reference to FIG. **41A**, a two-position, retractable centerbody aft-cone **5022B** is employed for mode transition. The retractable centerbody aft-cone **5022B** is fully extended rearward, as is depicted in the portion of the figure above the centerline, during non-afterburning operation to maintain low pressure loss by keeping the flow attached to the aft cone, and is fully retracted forward, as is depicted in the portion of the figure below the centerline, during afterburning operation to provide flow separation with a robust central recirculation zone that is required for flameholding and rapid flame spreading. The housing of the centerbody **5022A** has an annular thickness (i.e., defines an annular wall) that contains the manifolds for the fuel injection sites **5028**. Various means may be employed to actuate (i.e., extend and retract) the retractable centerbody aft-cone **5022B**, such as internal hydraulic or pneumatic actuators that may, for example, be fuel driven. As another alternative, the retractable centerbody aft-cone **5022B** may be actuated via a conventional and well-known jackscrew type actuator. Support and guidance for the retractable centerbody aft-cone **5022B** may be provided by the actuator and the housing of the centerbody **5022A**. In the retracted position, although a portion of the housing of the centerbody **5022A** is exposed when the retractable centerbody aft-cone **5022B** is retracted, the fuel flowing through it to the fuel injection sites **5028** functions as a coolant which cools the housing of the centerbody **5022A**.

Because the afterburner **5020** is able to operate at flame-spreading velocities that are over four times greater than those attainable by the conventional afterburner **5000**, combustion in the afterburner **5020** is completed in a considerably shorter distance, and therefore it becomes compact, lighter in weight and more fuel efficient than the conventional afterburners. Additionally, no aero-intrusive instream flameholders **5008** of FIG. **40** are required, because the flame stabilization and propagation processes are controlled by the aerodynamics of the swirling flowfield. No aero-intrusive fuel injection rings **5006** of FIG. **40** are needed either, because the fuel is injected from the trailing edges **5028** of the swirl vanes and the centerbody **5030**. The long tail cone **5004** is eliminated and replaced with a short centerbody **236r** having an extendable and retractable tapered cone **5022**, and variable angle swirl vanes **206r** to accommodate afterburning and non-afterburning modes of operation in order to maximize thrust output at all operating conditions.

The thermal control of the swirl-augmented afterburner could be performed using known combustor technology methods. These techniques would include: fuel scheduling to minimize heat flux to the walls; bypass air cooling, bleed, and film cooling to reduce the temperature of wall materials; and the use of high temperature alloys and materials to withstand the afterburner operating temperatures. Ceramic matrix and other high temperature/refractory materials can be used in localized zones. In addition, fuel injector faces and possibly portions of the exposed centerbody surfaces may be fuel cooled. A specific design would utilize multiple approaches to minimize thermal issues and provide increased service life at the lowest cost.

While the invention has been described in the specification and illustrated in the drawings with reference to various preferred embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention as defined in the claims. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the

27

invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment illustrated by the drawings and described in the specification as the best mode presently contemplated for carrying out this invention, but that the invention will include any embodiments falling within the foregoing description and the appended claims.

What is claimed is:

1. An engine assembly comprising:

a gas turbine engine producing an exhaust flow; and
an afterburner apparatus coupled to the gas turbine engine, the afterburner apparatus including a combustor, a swirl generator and a variable area nozzle, the combustor having a combustor inlet, the swirl generator having an inlet housing, a swirl vane pack, a centerbody assembly, and a plurality of fuel injectors, the inlet housing being coupled to the combustor inlet, the inlet housing defining a hollow interior volume therein and serving as a conduit through which at least a portion of the exhaust flow is conducted, the hollow interior volume intersecting the combustor inlet at a dump step wherein the inlet housing has an inner dimension that is smaller than that of the combustor inlet, the swirl vane pack being disposed within the hollow interior volume and having a plurality of vanes, the vanes cooperating to change the velocity of the exhaust flow so that its velocity includes a substantial tangential velocity component, the centerbody assembly being coupled to the swirl vane pack and extending rearwardly therefrom, the plurality of fuel injectors being coupled to at least one of the inlet housing, the swirl vane pack and the centerbody assembly and dispensing a fuel therefrom;

wherein the swirl generator converts the exhaust flow received therein into a swirling, three-dimensional flowfield;

wherein a first portion of the flowfield flows over the dump step to form an outer recirculation zone;

wherein a second portion of the flowfield forms a central recirculation zone that is anchored by an aft end of the centerbody assembly;

wherein a first portion of the fuel mixes with the first portion of the flowfield to fuel the outer recirculation zone;

wherein a second portion of the fuel mixes with the second portion of the flowfield to fuel the central recirculation zone;

wherein a remaining portion of the fuel enters and fuels a core flow; and

wherein the variable area nozzle receives combustion byproducts produced in the combustor by combustion of the fuel and produces propulsive thrust in response thereto.

2. The engine assembly of claim 1, wherein at least a portion of the fuel injectors are positioned to inject the fuel downstream of the swirl vane pack.

3. The engine assembly of claim 1, wherein at least one of the fuel injectors is housed in the centerbody assembly.

4. The engine assembly of claim 3, wherein the centerbody assembly includes at least one injection ring, the injection ring including a plurality of fuel injection sites that are spaced apart about a perimeter of the injection ring.

5. The engine assembly of claim 3, wherein the at least one of the fuel injectors is coupled to an aft end of the centerbody assembly and is configured to inject fuel in a direction downstream of the centerbody assembly.

28

6. The engine assembly of claim 1, wherein the plurality of fuel injectors include a plurality of fuel injection sites that are formed into at least a portion of the vanes of the swirl vane pack.

7. The engine assembly of claim 6, wherein each vane includes a trailing edge and a lateral surface and wherein the fuel injection sites on a given vane are formed into at least one of the trailing edge and the lateral surface.

8. The engine assembly of claim 1, wherein the centerbody assembly terminates at an aft bluff boat-tail body, the aft bluff boat-tail body being configured to augment flow separation of the exhaust flow.

9. The engine assembly of claim 8, wherein the centerbody assembly includes an extendable centerbody cone.

10. The engine assembly of claim 1, wherein the vanes of the swirl vane pack are selectively positionable at a first position and a second position.

11. The engine assembly of claim 10, wherein the vanes are further selectively positionable to at least one position between the first and second positions.

12. The engine assembly of claim 10, wherein the first position is an orientation of 0° so as not to swirl the exhaust flow when the afterburner apparatus is not being employed.

13. The engine assembly of claim 10, wherein the second position is a non-zero orientation of the vanes that causes the exhaust flow to swirl.

14. The engine assembly of claim 10, wherein the vanes have a flat profile.

15. The engine assembly of claim 1, wherein the swirl generator further comprises at least one igniter, the igniter being coupled to one of the centerbody assembly, the inlet housing and the combustor, the igniter being operable for generating an ignition kernel that ignites the fuel/oxidizer mixture in the central recirculation zone.

16. The engine assembly of claim 15, wherein the igniter is housed in the centerbody assembly.

17. The engine assembly of claim 16, further comprising a second igniter coupled to the combustor at a location downstream of the dump step.

18. The engine assembly of claim 1, wherein the inlet of the combustor includes a quarl expansion.

19. The engine assembly of claim 1, wherein an inlet ramp is formed onto the inlet housing adjacent the dump step.

20. The engine assembly of claim 19, wherein a plurality of circumferentially spaced apart injection sites are formed into the inlet ramp, the injection sites comprising at least a portion of the fuel injectors.

21. The engine assembly of claim 1, wherein the vanes are configured to provide the swirl vane pack with a swirl number that is less than about 2.0.

22. The engine assembly of claim 1, wherein the combustor is an expanding combustor.

23. An apparatus for providing propulsive power comprising:

a gas turbine engine producing an exhaust flow; and
an afterburner apparatus having a combustor, a swirl generator and a variable area nozzle, the swirl generator being associated with an aft end of the gas turbine engine, the swirl generator including a flow affecting means and a fueling means, the flow affecting means including a plurality of vanes, a centerbody having an aft end that terminates rearwardly of a root of the vanes and a dump step, the flow affecting means being operable for converting the exhaust flow into a three dimensional flowfield that includes a substantial tangential velocity component, the flow affecting means being further operable for effecting both a toroidal

29

outer recirculation zone, which is anchored by the dump step, and a central recirculation zone that is disposed inwardly of the outer recirculation zone and anchored by the aft end of the centerbody, the fueling means being operable for fueling the outer and central recirculation zones and a core flow, the combustor being associated with an aft end of the swirl generator, the variable area nozzle being associated with an aft end of the combustor;

wherein heat and combustion byproducts produced during combustion are carried upstream by the outer and

30

central recirculation zones where the heat and combustion byproducts are employed to continuously ignite a combustible fuel/oxidizer mixture in a shear layer adjacent each of the outer and central recirculation zones; and

wherein combustion by-products from the core flow are expelled through the variable area nozzle to produce thrust.

* * * * *